



Fischbach-Compact-Gebläse einseitig saugend mit außenliegendem Motor - Typ CE/CFE-NM

Zuordnung Gebläse - Frequenzumrichter

	Typ	Art. Nr.	Volumenstrom max. (m ³ /h)	Leistung max. (kW)	Spannung (V)	Strom max. (A)	Drehzahl (U/min.)	Zuordnung Frequenzumrichter Typ
1	CFE540 / NM 0.55	8021583	1800	0,55	400 (230)	1,33	1421	L200-007NFE
2	CFE640 / NM 0.75	8021603	2080	0,75	400 (230)	1,71	1430	L200-007HFE
3	CE670 / NM 1.1	8021033	2790	1,1	400 (230)	2,23	1442	L200-015HFE
4	CE690 / NM 1.5	8021043	3615	1,5	400 (230)	2,94	1446	L200-015HFE
5	CE790 / NM 2.2	8021053	4970	2,2	400	4,55	1452	L200-022HFE
6	CE890 / NM 3.0	8021073	6370	3,0	400	6,79	1434	L200-030HFE
7	CE990 / NM 5.5	8021093	8775	5,5	400	10,65	1456	L200-055HFE
8	CE9-090 / NM 7.5	8021103	10250	7,5	400	14,37	1458	L200-075HFE

	Typ	Art. Nr.	Gewicht in kg
1	CFE540 / NM 0.55	8021583	17,0
2	CFE640 / NM 0.75	8021603	19,0
3	CE670 / NM 1.1	8021033	21,0
4	CE690 / NM 1.5	8021043	26,0
5	CE790 / NM 2.2	8021053	34,0
6	CE890 / NM 3.0	8021073	42,0
7	CE990 / NM 5.5	8021093	68,0
8	CE9-090 / NM 7.5	8021103	78,0